

RMS 5.0 HOST COMPUTER REQUIREMENTS

- Microsoft® Windows 2000 sp4, Windows XP sp2, Windows Vista
- 500 MHz Pentium III; Pentium IV or faster recommended
- 256 MB of RAM; 512 MB recommended
- 55 MB of hard drive space
- CD or DVD drive for installation
- 800 x 600 display; 1024 x 768 recommended
- Internet access for RMS upgrade downloads

Supported Network Interfaces

The following network interfaces are supported by RMS 5.0:

ECHELON PCLTA-20 NETWORK INTERFACE CARD - requires a 32-bit PCI card slot, half- or full-size.

ECHELON PCC-10 NETWORK INTERFACE CARD - requires a Type II PC (PCMCIA) card slot.

ECHELON U10 USB NETWORK INTERFACE ADAPTER - requires a USB 2.0 or 1.1 port.

ECHELON I.LON 10 ETHERNET ADAPTER - requires an Ethernet (RJ-45) port.

Compatibility Notes

1. *The Echelon PCC-10 Network Interface card is not compatible with the following laptop computers: Dell™ Latitude C610, Gateway® Solo 5300, and Toshiba Satellite Pro 4600, 7600, and 8100.*
2. *RMS cannot be run from a wireless tablet or computer via an i.LON 10 Ethernet Adapter.*

